

Partial Translation of Exhibit 5
JP Application Laid-Open H3-176411
Laying Open Date, July 13, 1991

Partial Translation of Exhibit 5

JP Application Laid-Open H3-176411

Laying Open Date : July 31, 1991

Application No. : H1-314883

Application Date : December 4, 1989

Applicant : Kobayashi Kose Co.

Title of the Invention : Oily Solid Cosmetic

Claim:

1. An oily solid cosmetic comprising components from (A) to (C),

(A) 5 to 40 wt% of at least one solid wax selected from the group consisting of microcrystalline wax, polyethylene-polypropylene copolymer, polyethylene wax, ceresin wax, and paraffin wax,

(B) 1 to 30 wt% of at least one fine-grain powder selected from the group consisting of titanium oxide, zinc oxide, aluminum oxide, silicic acid anhydride, and iron oxide, said powder having a diameter of 0.1 mm or smaller,

(C) 30 to 80 wt% of liquid oil

and having a glossiness at 60° of both incident and reflection angles of 40 % or higher.

Specification

Examples of the polyethylene wax are Polywax 500, Polywax 655, ex BARECO co., and Uniwax, ex Nippon Petroleum Co.: An example of polyethylene-polypropylene copolymer is Petrolite CP-7, ex BARECO co.

Preferably, the solid wax is contained in an amount from 5 to 40 wt%, more preferably from 10 to 30 wt%, based on a total weight

of th composition. With an amount below 5 wt%, a solid cosmetic cannot be molded. With an amount above 40wt%, usability of a cosmetic is worse.